

LESLIE 9065 CONSOLE CONNECTOR KIT INSTALLATION INSTRUCTIONS

For use with: THOMAS 500,600, 700,800,900 Series
LESLIE 900 Speaker

MULTIPLE SPEAKER INSTALLATION: For complete information, see the service manual of the Leslie Speaker to be added.

CONTENTS OF KIT:

1	Console Connector	053439	
1	9-Conductor Cable	021600	1 Reverb Control
1	Oiler	053025	047118 Brown
1	Instructions	053470	047126 Ebony
2	Screws, 6 x 3/4, Black Oxide	032086	047134 Ivory

LESLIE CONTROLS:

A Tremolo control is not needed with this kit. Tabs at the Thomas control the Leslie's Tremolo and Chroale functions.

The earphone switch found beneath the lower manual of the Thomas turns the console speakers on and off.

TO INSTALL:

1. Remove back panel from the Thomas Organ.
2. Plug the console connector into Thomas amplifier socket marked: "THOMAS LESLIE 300 or 301 Tone Cabinet".
3. Mount Reverb control to underside of the Thomas lower manual. Use the two black oxide screws provided in the hardware kit.
4. Drill a one-inch hole through the Thomas keyboard shelf. Route Reverb Control Cable through this hole to the console connector.
5. Connect the Reverb control plug to the molex socket at the console connector.
6. Replace the Thomas back panel.
7. Connect the 9-conductor speaker cable to the console connector and the 900 Speaker power plug. Installation is now complete.

